

Easylink+



AUTOMATIC COUPLING STATION

Automatic coupling station able to manage up to 60 inlets/outlets with pipe size from 40 to 76 mm with minimum footprint.

Designed for easy maintenance, it is totally safe for the operators both during regular functioning and service activities.

The geometries, the advanced cleaning systems and the wear resistant materials assure the constant production quality in most demanding conditions.

Integration with Winfactory 4.0 allows:

- maximum traceability of materials
- automatic setting of transport and line cleaning times.

Easylink+ is available with supporting frame for floor or mezzanine installation.

All the internal pipe routing is realised with rigid piping, without any flexible hose.



Fast and precise



Ideal quality traceability



High flexibility

Diameter available

40, 50, 60 and 76 mm

Control

PLC control to manage the automatic coupling station, fully integrated with the feeding control Easy3/Easy3+

Options available

Inlet dedicated for cleaning with grid or with cartridge filter, painted steel or Plexiglas panels, individual slide gate for each outlet



The internal arm is equipped with a local cleaning device, in order to avoid risk of contamination in the common part of the circuit



Material database, sources, destination matrix and line recipes can be easily created in WF4.0 and use for the automatic setting of Easylink+



Pneumatic slide gates could be added as optional, preventing any risk of contamination

		Diam. 40 mm	Diam. 50 mm	Diam. 60 mm	Diam. 76 mm
Frame EL20	IN	20	20	20	16
	OUT	21	21	21	17
Frame EL40	IN	39	39	35	29
	OUT	40	40	36	30
Frame EL60	IN	59	59	52	-
	OUT	60	60	53	-